



L'huile des records du monde

MVX 1000 4T – SAE 5W-40

100 % synthetic oil for 4 stroke motorbike engines

USES

100 %synthetic engine oil especially recommended for motorbikes equipped with the latest technologies .

Maintains the engine performances in extreme driving conditions and in long distance journeys at high speed. Exceeds the requirements of main motorbikes manufacturers.

Recommended when the manufacturers specify the use of a SAE 5W40 engine oil (ex. BMW, PIAGGIO).

MAIN CHARACTERISTICS

		Units	SAE 5W-40
Density	20° C	kg/m ³	858
Kinematic viscosity	40° C	mm ² /s	92
Kinematic viscosity	100° C	mm ² /s	15.2
Viscosity Index			175
Pour Point		° C	-39
Flash Point Cleveland open cup		° C	>210
Dynamic viscosity	-30° C	mPa.s	6000


The data given in this table are typical production values and cannot be considered as specifications.

PROPERTIES & ADVANTAGES

- High friction coefficient in accordance with the JASO MA2 requirements, preventing clutch slipping and increased protection of the gear/clutch assembly
- 100 % synthetic formula for optimal protection at high temperature and reduction of oil consumption.
- SAE 5W-40 grade provides excellent stability at high temperature and quick lubrication at start up.
- Use of specific viscosity index improvers allowing exceptional shear stability. This keeps the viscosity in service and increases gear and engine protection
- Good detergent/dispersant capabilities keep engines clean.

HOMOLOGATION

JASO MA2



JASO T903-2011

PERFORMANCE IS GUARANTEED by
YACCO S.A.S.

SPECIFICATION

API SL

